F 153 SILENT-G

F 153 SILENT-G

For illustrative purposes only

ENGINE

Description	FPT IVECO	
Engine model	N67TE1PV	
Cylinders	6	
RPM speed	1500	
Cubic capacity	6.70	l
Air intake	Turbocharged	
Standard voltage	12	Vdc
Optional voltage	24	Vdc
Sae	3-11½	
BMEP	1629	kPa
Cooling	Water	
Flywheel P.R.P. Power net	131.5	kW
Flywheel E.P. Power net	145.0	kW
Fuel Cons. at 100% (E.P.)	37.9	l/h
Fuel Cons. at 100% (P.R.P)	34.0	l/h
Fuel Cons. at 75% (P.R.P.)	28.0	l/h
Fuel Cons. at 50% (P.R.P.)	18.9	l/h
Fuel Cons. at 25% (P.R.P.)	8.3	l/h
Electronic regulator	Standard	
Precision class	G3	
Oil quantity	17.20	l
Engine Antifreeze capacity	10.5	l
Radiator type	TR	
Heat from radiator	0.00	kW
Heat from exhaust	138.8	kW
Heat from radiation	0.00	kW
Exhaust temperature	490	°C
Cooling air flow	0.00	m³/min
Combustion air flow	10.73	m³/min
Exhaust gas flow	28.89	m³/min
TA Luft	N	
TA Luft/2	N	
EPA	N	
Stage	3	

MAIN DATA

Continuous power (PRP)	**150.00**	kVA
Continuous power (PRP)	**120.00**	kW
Emergency power (E.P.)	**165.00**	kVA
Emergency power (E.P.)	**132.00**	kW
VAC - HZ - cos(fi)	**400 - 50 - 0.8**	
Sound pressure 7 m.	**71.0**	dBA

DIMENSIONS AND WEIGHT

Width	1140	mm
Length	3060	mm
Height	2200	mm
Weight	2050	kg

ALTERNATOR

Description	STAMFORD	
Alternator model	UCI274F	
P.R.P. Power	160.0	kVA
E.P. Power	175.0	kVA
Connection	Series star	
Phases	3FN	
Winding	311	
Terminal Number	12	nr.
IP Protection	23	
Electronic regulator	AS440	
Precision	1.0	± %

BASEFRAME

Standard tank	360	l
Optional tank	120	l
Oversized tank*	800	l

CANOPY & SILENCER

Silencer model	MSR/a 80	
Silencer outlet diameter	89.0	mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **E.P. - Emergency power:** This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.